



# Plastic Shears

- **Splinterproof cutting of all synthetic resin and laminated plastic-materials:** Pk-Tex, Textolite, Formica, Perstorp, Ultrapas, Resopal, Celamin, Hornitex, Getalit, Novatex, Thermopal, Tacon, etc. \*\*
- **Fuzz and dust free cutting** Hardboard, Pavatex, Renovite, Karton, Masonit, Silvacolor, Hornitex, Glasal, etc. \*\*
- **Also:** Inlaid, Linoleum, Veneer, etc., Deliflex, Linoleum, Mipolam, PVC, Polyester (dust free!), etc. \*\*
- flush trimming of projected edges with side guide
- cutting of strips and edge-bands
- NO PLEXIGLAS !

- easy, one hand, operation
- simple and safe to use
- insulated and suppressed motor
- motor with a protective switch (S1002N)
- accurate cutting along a marked line
- clear view to scribed line or template
- long life tool
- can cause no injury while in motion
- noise under limit
- low maintenance
- knives and jaws can be exchanged or re-sharpened


## S1002N



flush trimming of projecting edges with side guide



assembling side guide with two wing screws



set of blocks, for straight cutting of corrugated plastics



S/02 adjustable guide for cutting strips or edge-bands

## 3550 – speed control



DRÄCO Plastic Shears	S1002N	3550
<b>max. cutting capacity</b>	Art.no. 61310	61320
Board etc.	mm/ga. <b>5,0</b>	<b>5,0</b>
PVC, ABS, PP, etc.	mm/ga. <b>3,0 / 10</b>	<b>3,5 / 9</b>
Polyester, GFK, Formica, etc.	mm/ga. <b>2,0 / 14</b>	<b>3,0 / 10</b>
Teflon, ABS, GFK, PVC etc.	better	with speed control
tightest radius	mm/° <b>175 / 7</b>	<b>175 / 7</b>
working speed	m/min <b>6</b>	<b>0 - 5</b>
strokes	min <sup>-1</sup> <b>3000</b>	<b>2400</b>
motor capacity	Watts <b>200</b>	<b>500</b>
weight	kg <b>1,6</b>	<b>2</b>

S1002N & TYP II	3550
<b>spare parts</b>	<b>spare parts</b>
knife 01002	knife 01002
set of jaws BG20600	set of jaws BG20601
knife-pin set BG12555	knife-pin set BG12555
<b>optional accessories</b>	
metal-box	18000
adjustable guide S/02 up to 100 mm	20062
adjustable guide S/02 up to 250 mm	20063
adjustable guide S/02 up to 500 mm	20064
set of blocks for corrugated plastics	BG20065

all units are ready to use

\*\* Trademarks

BG=Set

other voltages available