

PN 4360

PN 4361

Cold and emission-free operation PN 4360: profile height up to 79 mm PN 4361: profile height up to 162 mm

Common features:

- extremely manoeuvrable, easy operation
- fast, safe cutting of corrugated, trapezoidal and square sheet profiles
- welded seams and double sheet can be cut, even corners with acute angles
- high cutting capacity
- chips eject below material, guarantees clear, unimpeded view of the working area and the cutting line
- cuts all materials that can be punched, such as mild steel, stainless steel aluminium, non ferrous metals and plastics
- tooling system allows cutting direction to be changed as required
- Iong life tools
- regrind able, easy to change tooling
- superior, emission-free operation
- free from sparks or heating
- no damage or scratch marks to painted or coated materials

Ideal for:

- halls, factories, roof and wall in corrugated materials
- I roofers
- shop installation, etc.

Also available:

➔ cordless, 18 Volt, AK 3160 Li-Ion and AK 3161 Li-Ion

DRÄCO Profile Nibblers		type	PN 4361	PN 4360
max. cutting capacity		Art.no.	61220	61210
steel	400 N/mm ²	mm/ga.	1,6 / 16	2,0 / 14
stainless steel	600 N/mm ²	mm/ga.	1,0 / 19	1,2 / 18
stainless steel	800 N/mm ²	mm/ga.	0,7 / 21	1,0 / 19
non ferro	250 N/mm ²	mm/ga.	2,5 / 12	2,5 / 12
depth of profiles max.		mm/ "	162 / 61 / ₂	79/3
tightest radius		mm/ "	50 / 2	70 / 2¾
starting hole		mm/ "	24 / 1	24 / 1
working speed		m/min	2	2
strokes		min ⁻¹	0-1400	0-1400
motor capacity		Watts	500	500
weight		kg	2,0	1,8

PN 4361 & PN 4360	
spare parts	
punch	41576
die	41577
wear plate	41579
screw (Torx)	41022

optional accessories	
transport-box for PN 4361	42861
metal-box for PN 4360	18000
nibbling oil (bottle 1,0L)	20198
nibbling oil (spray 0,5L)	20199

all units are ready to use

speed control available in 230V only

other voltages available