

Cordless Shears and Nibblers System 3000 Ni-Cd / NiMH

Common features:

- ergonomic designed motor
- Power Plus motor: 30% more power
- 2,0 Ah 24,0 Wh highest quality, long life battery packs
- cutting up to 120 meters with one battery charge
- universal super-rapid charger SRC (15 min)
- charger is suitable for charging all systems 3000 battery packs
- computer controlled pulse charging technology charges batteries quickly and gently, leading to a threefold increase in life of battery packs
- fail-safe polarity protection
- fully automatic functions: continuous temperature monitoring and switching from quick charge to trickle charge make overcharging impossible!
- LED control panel reports charging status or malfunction
- in conjunction with battery charger SRC, batteries can be charged 3000 times or more no "memory effect"



Slitter Shear








Batteries BXS 2.0Ah

MXL 12, or 14.4 3.0Ah Chargers SRC or RC

5-pcs. craftsmen-set consists of:

- 1 shear or nibbler
 - 1 charger SRC (15 min.)
- 2 batteries BXS
- 1 transportbox



- 1 shear or nibbler
 - 1 charger RC (60 min.)
 - 1 battery BXS
 - 1 transportbox



Transport box 42861

| DRÄCO Cordless Ni-Cd Shears | | | AK 3010 | AK 3013 | AK 3016 | AK 3520 | AK 3514-2 | AK 3514-7R |
|----------------------------------|-----------------------|--------|----------|------------|----------|----------|-----------|------------|
| Item number 5-pcs.craftsmen-set: | | | 30103 | 30133 | 30163 | 35203 | 351423 | 351473 |
| max. cutting capacity | | | | | | | | |
| steel | 400 N/mm ² | mm/ga. | 1,0 / 19 | 1,3 / 18 | 1,6 / 17 | 2,0 / 14 | 2,0 / 14 | 2,0 / 14 |
| stainl.steel | 600 N/mm ² | mm/ga. | 0,7 / 21 | 1,0 / 19 | 1,3 / 18 | 1,3 / 18 | 1,3 / 18 | 1,3 / 18 |
| stainl.steel | 800 N/mm ² | mm/ga. | 0,4 / 25 | 0,7 / 21 | 1,0 / 19 | 1,0 / 19 | 1,0 / 19 | 1,0 / 19 |
| non ferro | 250 N/mm ² | mm/ga. | 1,5 / 17 | 2,0 / 14 | 2,5 / 12 | 2,5 / 12 | 2,5 / 12 | 2,5 / 12 |
| tightest radius ±mm/ " | | 50 / 2 | 100 / 4 | 140 / 51/2 | 200 / 8 | 200 / 8 | 45 / 13/4 | |
| working speed ±m/min | | ±m/min | 3,5 | 3,5 | 3,5 | 4 | 4 | 4 |
| strokes ±min -1 | | 1800 | 1800 | 1800 | 1800 | 1800 | 1800 | |

operational field of the cordless shears: see the electric versions SD5-1, S1001N-1, 1016-1, 3520, 3514-2 & 3514-7R.

| DRÄCO Cordless Nibblers Item number 5-pcs.craftsmen-set: | | | AK 3160 | AK 3161 | AK 3200 |
|---|-----------------------|---------------------|----------|----------|----------|
| | | | 31603 | 31613 | 32003 |
| max. cutting | capacity | | | | |
| steel | 400 N/mm ² | mm/ga. | 1,6 / 17 | 1,6 / 17 | 2,0 / 14 |
| stainl.steel | 600 N/mm ² | mm/ga. | 1,0 / 19 | 1,0 / 19 | 1,5 / 17 |
| non ferro | 250 N/mm ² | mm/ga. | 2,5 / 12 | 2,5 / 12 | 2,5 / 12 |
| tightest radius ± mm/inch | | | 50 / 2 | 70 / 2 ¾ | 4 / 1/8 |
| working speed ± m/min | | ± m/min | 1 | 1 | 1 |
| strokes ± min -1 | | ± min ⁻¹ | 1200 | 1200 | 1200 |

operational field of the cordless nibblers: see the electric versions PN 4360, PN 4361 & PN 4320.

Note: Due to temperature and material, cutting capacity per battery charge can be over- or under the average.

all units are ready to use


other voltages for chargers available, see price list



Cordless System 3000 overview

AK 3010

- ideal for tin smiths and roofers
- accurate curve and burr-free cutting
- knife and jaws can be re-sharpened and exchanged
- shear head equivalent to SD5-1



- ideal for site work
- burr-free cutting
- shear blade head with regrind able and exchangeable blades
- shear heads equivalent to S1001N-1 resp. 1016-1



- ideal for all shop installation, for example: cutting cable trays, steel studs
- knife and jaws can be re-sharpened and exchanged
- shear head equivalent to 3520



- spiral ducting
- roof & wall claddings
- through seams 6 times folded
- mesh and wire
- shear head AK 3514-2 equivalent to 3514-2
- shear head AK 3514-7R equivalent to 3514-7R

AK 3200

- excellent curve negotiation and narrow cutting radius
- rotating tool system allows changing cutting direction 360° without difficulties
- shear head equivalent to PN 4320

















AK 3161 (long version)

- corrugated materials up to 162 mm deep profiles
- shear head equivalent to PN 4361

AK 3160 (short version)

- corrugated materials up to 79 mm deep profiles
- shear head equivalent to PN 4360

